

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: Potassium silicate 4009

Unique Formula Identifier (UFI): 6600-E0MV-G007-55GS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Industiral use in the chemical /fertiliser /photographic /Offshore industry as such (substance itself) or in a mixture. Paint Washing product

SU: Sector of Use (SU):

PC: Adhesives, sealants (PC1) Coatings and paints, thinners, paint removers (PC9a) Fillers, putties, plasters, modelling clay (PC9b) Metal surface treatment products (PC14) Non-metal-surface treatment products (PC15) Hydraulic fluids (PC17) Leather treatment products (PC23) Lubricants, greases, release products (PC24) Paper and board treatment products (PC26) Photo-chemicals (PC30) Semiconductors (PC33) Textile dyes, and impregnating products (PC34) Washing and cleaning products (PC35) Cosmetics, personal care products (PC39)

PROC: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. (PROC1). Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2). Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3). Chemical production where opportunity for exposure arises (PROC4). Mixing or blending in batch processes (PROC5). Calendering operations (PROC6). Industrial spraying (PROC7). Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a). Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b). Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9). Roller application or brushing (PROC10). Non industrial spraying (PROC11). Treatment of articles by dipping and pouring (PROC13). Tableting, compression, extrusion, pelletisation, granulation (PROC14). Manufacturing and processing of minerals and/or metals at substantially elevated temperature (PROC22). Open processing and transfer operations at substantially elevated temperature (PROC23). High (mechanical) energy work-up of substances bound in /on materials and/or articles (PROC24).

Inadvisable uses: None. None.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company: Bollerup Jensen A/S
Address: Bindsbølvej 16-20, Ådum
Zip code: 6880
City: Tarm
Country: DENMARK
E-mail: info@bollerup-jensen.dk
Phone: +45 9737 6033
Homepage: www.bollerupjensen.dk

1.4. Emergency Telephone Number

Members of the public: 111 (NHS 111 (Scotland: NHS 24))

SECTION 2: Hazards identification

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

2.1. Classification of the substance or mixture

CLP-classification: Skin Irrit. 2;H315 Eye Irrit. 2;H319
Most serious harmful effects: Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Pictograms



Signal word: Warning

H-phrases

H315 Causes skin irritation.
H319 Causes serious eye irritation.

P-phrases

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective glove/eye protection.
P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local regulations.

Supplemental information

Safety data sheet available for professional users on request.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
Potassiumsilicate MR >3,2 (lumps)	1312-76-1	215-199-1	01-2119456888-17-xxxx	25 - 50%		
potassium hydroxide 50%	1310-58-3	215-181-3	01-211948713-6-33	< 2%		Met. Corr. 1;H290 Acute Tox. 4;H302 Skin Corr. 1A;H314

Please see section 16 for the full text of H-phrases.

Ingredient comments: Solutions: 3.2>=MR>2.6

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air.
Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Seek medical advice immediately.
Skin contact: Wash the skin with water.
Eye contact: Open eye wide, remove any contact lenses and flush immediately with water (preferably using eye wash equipment). Seek medical advice immediately. Continue flushing until

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

medical attention is obtained.

General: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

May cause eye irritation. May irritate the skin - may cause reddening. If ingested, can be irritating to mucous membranes of the mouth and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: The product is not directly flammable. Choose extinguishing agents based on the surrounding fire.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is not directly flammable. Avoid inhalation of vapour and fumes - seek fresh air.

5.3. Advice for fire-fighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stop leak if this can be done without risk. Wear safety goggles. Wear gloves.

For emergency responders: Normal protective clothing equivalent to EN 469 is recommended.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers. Wipe up minor spills with a damp cloth. Rinse with water.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Running water and eye wash equipment must be available. A safety shower should be available. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Keep in tightly closed original packaging. The product should be stored safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Store frost-free.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Substance name	Time period	ppm	mg/m ³	fiber/cm ³	Comments	Remarks
potassium hydroxide 50%	15m		2			

Measuring methods: Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

Legal basis: EH40/2005 Workplace exposure limits. Last amended January 2020.

DNEL - workers

potassium hydroxide 50%, cas-no 1310-58-3					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	1 mg/m ³				

DNEL - general population

potassium hydroxide 50%, cas-no 1310-58-3					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	1 mg/m ³				

8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles.

Personal protective equipment, skin protection: Wear suitable protective clothing.

Personal protective equipment, hand protection: Wear gloves. Type of material: Nitrile rubber/ Neoprene rubber/ Butyl rubber/ Rubber.

Personal protective equipment, respiratory protection: Not required.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Liquid
Colour	Transparent Clear
Odour	Odourless
Solubility	Miscible with the following: Water.
Explosive properties	No data
Oxidising properties	No data

Parameter	Value/unit	Remarks
-----------	------------	---------

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

pH (solution for use)	13	
pH (concentrate)	No data	
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flash Point	No data	
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	No data	
Vapour pressure	No data	
Vapour density	No data	
Relative density	1.35 - 1.65 g/cm ³	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
Viscosity	No data	
Odour threshold	No data	

9.2 Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts under heat generation with the following: Acids.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

May react powerful by contact with acids and metals.

10.4. Conditions to avoid

Avoid direct sunlight.

10.5. Incompatible materials

Avoid contact with the following: Acids/ Metals.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral: Ingestion may cause discomfort.

Acute toxicity - dermal: No hazards.

Acute toxicity - inhalation: No hazards.

Skin corrosion/irritation: Irritating to skin - may cause reddening.

Serious eye damage/eye irritation: Irritating to eyes. Causes a burning sensation and tearing.

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

Respiratory sensitisation or skin sensitisation:	No hazards.
Germ cell mutagenicity:	No mutagenic effects observed.
Carcinogenic properties:	No carcinogenic effects observed.
Reproductive toxicity:	No indications.
Single STOT exposure:	No hazards.
Repeated STOT exposure:	No hazards.
Aspiration hazard:	Test data are not available.
Other toxicological effects:	None known.

SECTION 12: Ecological information

12.1. Toxicity

Occasional major emissions or frequently recurring minor emissions may have a harmful or disturbing effect.

12.2. Persistence and degradability

Readily biodegradable.

12.3. Bioaccumulative potential

No bioaccumulation expected.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

The product affects the pH value of the local aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Collect concentrated spills and major waste in closed, leak-proof containers for disposal at the local hazardous waste site. Do not discharge large quantities of concentrated spills and residue into drains. Uncleansed packaging is to be disposed of via the local waste-removal scheme.

Category of waste: EWC code: Depends on line of business and use, for instance 06 02 99 wastes not otherwise specified

SECTION 14: Transport information

14.1. UN-No.:	Not applicable.	14.4. Packing group:	Not applicable.
14.2. UN proper shipping name:	Not applicable.	14.5. Environmental hazards:	Not applicable.
14.3. Transport hazard class(es):	Not applicable.		

14.6. Special precautions for user

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

None.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not included.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: Regulation (EC) of the European Parliament and on the Council no. 1272/2008. Council Directive (EC) on the protection of young people at work. Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	28/10/2020	MBK	

Abbreviations: DNEL: Derived No Effect Level PNEC: Predicted No Effect Concentration STOT: Specific Target Organ Toxicity PBT: Persistent, Bioaccumulative and Toxic vPvB: Very Persistent and Very Bioaccumulative

References to literature and data sources: CEES (Centre Européen d'Etude des Silicates) June 2014 ECHA reg. sub.: ECHA database for information on registered substances.

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Training advice: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method: Expert judgement. Calculation based on the hazards of the known components. Test has shown that the product, despite extreme pH, is not corrosive.

List of relevant H-statements

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

SDS is prepared by

Company: Bollerup Jensen Group A/S
Address: Bindsbølvej 16-20
Zip code: 6880
City: Tarm
Country: DENMARK
E-mail: info@bollerup-jensen.dk

Safety Data Sheet

Potassium silicate 4009

Version: 1.0.0

Homepage: www.bollerupjensen.dk

Document language: GB

Print date: 26/11/2020